

### SH01 - Swivel Hanger

**Size Range:** 1/2" through 8"

**Material:** Carbon steel

**Finish:** Galvanized, other finish available upon request

**Service:**

- Recommend for suspension of non-insulated stationary pipe line
- Manufactured to use the min. rod size permitted by NFPA for fire sprinkler pipe line

**Approvals:**

- Complies with Federal Specification A-A-1192A (Type 10) WW-H-171-E (Type 10) and MSS-SP-69 (Type 10).
- FM approved & UL/ULC Listed (Sizes 3/4" through 8")

**Ordering:** Specify Part Number

Part Number	Nominal Pipe Size		RS		A		B		Wt.		Max. Rec. Load	
	In.	mm	In.	mm	In.	mm	In.	mm	lb	kg	Lbs	N
	SH01-015	1/2	DN15	3/8	M10	2 <sup>3</sup> / <sub>4</sub>	70	1	25	0.09	0.04	500
SH01-020	3/4	DN20	3/8	M10	3 <sup>1</sup> / <sub>16</sub>	78	1	25	0.09	0.04	500	2220
SH01-025	1	DN25	3/8	M10	3 <sup>5</sup> / <sub>16</sub>	84	1	25	0.10	0.05	500	2220
SH01-032	1 <sup>1</sup> / <sub>4</sub>	DN32	3/8	M10	3 <sup>9</sup> / <sub>16</sub>	90	1	25	0.10	0.05	500	2220
SH01-040	1 <sup>1</sup> / <sub>2</sub>	DN40	3/8	M10	3 <sup>13</sup> / <sub>16</sub>	97	1	25	0.11	0.05	500	2220
SH01-050	2	DN50	3/8	M10	4 <sup>1</sup> / <sub>4</sub>	108	1	25	0.12	0.06	500	2220
SH01-065	2 <sup>1</sup> / <sub>2</sub>	DN65	3/8	M10	4 <sup>7</sup> / <sub>8</sub>	124	1	25	0.27	0.12	1000	4440
SH01-080	3	DN80	3/8	M10	5 <sup>11</sup> / <sub>16</sub>	144	1	25	0.32	0.14	1000	4440
SH01-100	4	DN100	3/8	M10	6 <sup>7</sup> / <sub>8</sub>	174	1	25	0.38	0.17	1000	4440
SH01-125	5	DN125	1/2	M12	8 <sup>3</sup> / <sub>16</sub>	208	1 <sup>1</sup> / <sub>4</sub>	32	0.56	0.25	1900	8450
SH01-150	6	DN150	1/2	M12	9 <sup>5</sup> / <sub>8</sub>	245	1 <sup>1</sup> / <sub>4</sub>	32	0.67	0.31	1900	8450
SH01-200	8	DN200	1/2	M12	12 <sup>5</sup> / <sub>16</sub>	313	1 <sup>1</sup> / <sub>4</sub>	32	0.78	0.35	1900	8450

