

FICHA TECNICA

ABRAZADERAS MAXIMA



INOXIDABLE-316

ABRAZADERAS MAXIMA
ACERO INOXIDABLE 316 PULIDO BRILLANTE



TIPO	DESCRIPCION	RANGO MM	ESPESOR MM	ANCHO MM
3	ALTO TORQUE	17-19	0,8	20
4	ALTO TORQUE	20-22	0,8	20
5	ALTO TORQUE	21-23	0,8	20
6	ALTO TORQUE	23-25	0,8	20
7	ALTO TORQUE	25-28	0,8	20
8	ALTO TORQUE	26-29	1	24
9	ALTO TORQUE	29-32	1	24
A	ALTO TORQUE	32-35	1	24
B	ALTO TORQUE	35-38	1	24
C	ALTO TORQUE	38-43	1	24
D	ALTO TORQUE	42-45	1	24
E	ALTO TORQUE	44-47	1	24
F	ALTO TORQUE	46-51	1	24
G	ALTO TORQUE	50-54	1	24
H	ALTO TORQUE	52-57	1	24
I	ALTO TORQUE	56-63	1	24
J	ALTO TORQUE	61-68	1	24
K	ALTO TORQUE	68-74	1	24
L	ALTO TORQUE	74-80	1	24
M	ALTO TORQUE	79-86	1	24
N	ALTO TORQUE	86-93	1	24
Ñ	ALTO TORQUE	91-99	1	24
O	ALTO TORQUE	97-106	1	24
P	ALTO TORQUE	104-112	1	24
Q	ALTO TORQUE	110-120	1	24
R	ALTO TORQUE	116-125	1	24
S	ALTO TORQUE	124-132	1	24
T	ALTO TORQUE	130-138	1	24
U	ALTO TORQUE	138-146	1	24
V	ALTO TORQUE	146-155	1	24
W	ALTO TORQUE	155-163	1	24
X	ALTO TORQUE	163-174	1	24
Y	ALTO TORQUE	174-187	1	24
Z	ALTO TORQUE	187-200	1	24